



Handhabung

IC Card Reader

Contact (ISO 7816
EMV L1&L2)
/ Contactless
(ISO 14443 A/B/Mifare)



PCI Pin Pad Package

+ PCI PIN PAD
via Serial, USB or Bluetooth

Can be connected to
most PCI Pin Pads
with a single cable



MSR

Bi-directional magnetic
stripe reader certified with
ISO 7810 Track 1, 2, 3



Barcode Reader

Versatile barcode scanner
supporting 1D Laser or
1D & 2D Linear CMOS



Touchscreen

One touch access to
all your data and files



Printer

Conveniently large
2" thermal printer for
transaction receipts



Camera

Flash supported
2MP camera



SD Card Slot

Large memory capacity
with expandable
SD card slot



Zubehör



Spezifikationen

CPU	Intel Bulverde PXA270 520MHz
OS	Windows Mobile 5.0 Premium Phone Edition or Windows CE 5.0
Display	3.5 Inch 240 x 320 pixel QVGA Resolution, 260K Color TFT LCD
Memory	RAM: 128MB / ROM: 128MB, 256MB
Radio	GSM / GPRS / EDGE (Quad Band) & WLAN (802.11b/g), GPS (Optional) or CDMA (1x or EVDO) & WLAN (802.11b/g)
GPS	SiRF III Chipset Adopted
Input	Touchscreen, Numeric Keypad, Function Keys
Antenna	Internal Antenna: GSM, Quad Band, CDMA, WLAN, Bluetooth
Interface	PDA: USB Host & Client, IrDA, Bluetooth Class 2, 3SAMS, 1SIM, SD Card Slot CRADLE: RS-232C, USB Port MSR : ISO 7810 Track 1, 2, 3, Bi-Directional
Card Reader	IC Card Reader : Contact Type, ISO 7816 EMV Level 1, 2 Certified Contactless Type, ISO 14443 A / B / Mifare
Printer	2 Inch Thermal Printer
Barcode Engine	1D Laser or 1D & 2D (only PDF417) Linear CMOS
Camera	2 Megapixel, Flash Supported
Battery	7.4V 2000mAh Li-ion Battery (2000mAh X 2 Cell)
Dimension	218 x 87 (min 74) x 56.2 (min 29) / 510g (417g Battery Excluded)
Relative Humidity	5% to 95% RH Non-Condensing
Accessories	Battery, Cradle, Adapter, Protection Film, Power Cable, USB Cable, Handstrap, Tether, Stylus Pen